



Ameritek T1000

Tabber/ Labeler/ Stamp Affixer



T1000 (Standard) left to right paper path



T1000 (Optional) right to left paper path

- * ***Heavy duty construction for reliability and durability.***
- * ***Meet all requirements of owner, operator and USPS.***
- * ***Quick and simple job setups.***
- * ***Microprocessor controlled tab placement.***
- * ***Available in both left to right and right to left configurations.***
- * ***Available with product wrap on front (Standard) or rear.***

Ameritek T1000 Tabber/ Labeler/ Stamp Affixer

TECHNICAL SPECIFICATIONS

Configurations

Standard 1½" tabbing head
Left to right or right to left configurations
Available. Also available with product warp on the rear side of unit.

Speeds

Production Rates based on 8½" product length.

Single Tab: Up to 20,000 pieces/hour
Double Tab: Up to 15,000 pieces/hour
Triple Tab: Up to 12,000 pieces/hour

Transport Belt: 0 to 300 feet/minute
Tabbing Head: 0 to 300 feet/minute

Product Size

Minimum: 3" x 5"
Maximum: 13½" x 17"
Minimum Thickness: 20 # folded sheet
Maximum Thickness: 3/8"

Tabs/ Labels/ Stamps

Self adhesive on roll with 3" core and minimum 1/16" gap between tabs, labels, or stamps.

Minimum Width: ¾" backer width
Maximum Width: 1¾" backer – Standard
Minimum Pitch: ¾"
Maximum Pitch: 4"

Types: tabs, labels, stamps, scratch-offs, customized stickers, machine grade paper, clear or translucent.

Note: Clear and translucent tabs require an "engineered backer" with printed registration marking for indexing.

Roll Size: Up to 13½" diameter mounted on a 3" core.

Approx. Roll Capacity: 20,000 - 1" tabs or
12,500 - 1½" tabs

Tab Placement

Accuracy: +/- 1/8" repeatability

Physical Size

System Length: 34½"
System Width: 28"
System Height: 38"
Tabletop Height: 8½"
Weight: Approximately 160 lbs.

Electrical Requirements

115 VAC 50/60 Hz @ 5 Amps or
230 VAC 50/60 Hz @ 3 Amps

The Ameritek T1000 Table Top Tabber applies tabs, labels, stamps and scratch-offs to a wide variety of media including tri-fold brochures, newsletters, small catalogs and many others. It is designed for professional mailers, commercial printers, fulfillment houses or anyone else requiring a heavy-duty high quality Tabber/ Labeler/ Stamp Affixer.

It has front panel controls that are easy to use, making it simple to set up jobs or to switch between applications.

The Ameritek T1000 can be used inline with most friction feeders, inkjet print systems, conveyors and even some folders. It can also be run offline with a feeder in stand alone operation.



The Ameritek T1000 can also be configured as a Dual Headed Tabber. This system can tab on the leading (toe) and trailing (heel) edges of a booklet in a single pass. The Dual Headed Tabber can run in-line or off-line as a system, or the Tabbers can be unlocked and used as stand-alone units.

TY PAC
Inc.

PO Box 425
Baldwinsville, NY 13027
800 356-8964 315 638-9431

FAX 315 638-9433
www.typac.net
info@typac.com

