



SECAP[®] 2020 DUAL TABBER

SINGLE OR DOUBLE TAB AFFIXER

- High Speed Operation
- Paper & Clear Tabs
- Accurate Registration



TECHNICAL SPECIFICATIONS

Production Rate

Up to 21,000 pieces/hr. (single or double tabs)

Media Size

Width: Height: Thickness

4" to 8.5" up to 1/8"

6" to 11"

Type of Tabs Pinfed, 1" pitch repeat, round, paper or clear, 3" core.

Electrical Requirements 115V / 60 hz, 1.6A


Physical Characteristics: Dimensions: 18"W x 21"D x 13"H Weight: 86 lbs.

Certification: UL, FCC, IEC

Options:

21" on demand conveyor Ask about our supply of tabs.

(Specifications subject to change without notice.)



Model 2020 Dual Tabber shown with optional conveyor for improved handling of media.





Tab applications: single tab, flat or gate tab, double tab.

3. Continuous Feeding of Material

Stacking tray holds up to 6" capacity of media.

Simple push button controls on easy to read LCD

display. Job count and permanent count standard.

Batch count mail delivery-compatible. Detectors for cover open, misfeed and out of tabs.

Optional 21" on demand conveyor quickly moves

job along. Allows for easy batch sorting and

Top load, continuous feed feeder.

4. Operator Controls

5. On Demand Conveyor

enhances greater productivity.

DETAILS

The 2020 Dual Tabber can apply one or two tabs in one pass based on the media requirements. Dual tab application eliminates the need for running jobs through twice, speeding up processing time and improving productivity. The 2020 Tabber offers high quality construction, fast operating speeds and accurate tab application all from a tabletop machine.

1. Single or Dual Tab Application

Applies one or two tabs in a single pass. Tab reel holds 1" pinfed tabs or wafer seals, round, paper or clear with 3" core. Accommodates up to 10,000 tabs per reel.

2. Versatile Unit

- · Clear tab capable.
- · Sliding tab head for tab position adjustment.
- Flat tab for gate-fold mailer.

Ask about Secap's complete line of mailstream solutions:



Available from your authorized and certified Secap dealer.





Mailstream Management and Solutions...

10 Clipper Road West Conshohocken, PA 19428-2721 800.523.0320 610.825.6205 610.825.1397 (fax) www.secap.com

Contact the dealer above or call 800.523.0320 for a Secap dealer near you.