

SM2000...High speed, reliable strapping, at an affordable price

The SM2000 strapper is designed to provide high speed, jam resistant operation for a broad range of general purpose strapping applications at an affordable price. It is loaded with standard features, and can strap 50 times a minute using affordable 5, 6 or 9mm polypropylene strapping. The SM2000 is ideal for mailroom applications, distribution centers, publishing and forms. It is backed by a robust warranty, a complete parts inventory, and our own in house service department. Standard features include:

- Auto Strap Loading**
 The SM2000 loads with the touch of a button.
- Loop Ejector and Auto Re-Feed**
 Non completed cycles are automatically cleared and re-fed.
- One-Piece Strap Track**
 The unique, fully accessible, strap track reduces strap dust and applies consistently parallel straps.
- Electric Photo Eye**
 Standard on the SM2000, the adjustable photo eye gives you several automatic strapping options.
- 4 Modes of Activation**
 The strap cycle can be activated by photocell, magnetic palm switch, remote foot pedal or foot bar.
- Fast and Economical**
 Up to 50 cycles per minute of low cost 5, 6, or 9mm strap.
- Low Maintenance**
 The SM2000 has 30% fewer moving parts than comparable machines, uses brushless DC motors, and requires minimal lubrication.
- Portable Design**
 Four heavy-duty casters (two locking), compact design, and 110volt power makes the SM2000 easy to set up at any location.



TECHNICAL SPECIFICATIONS

Dimensions (Standard Arch): 32.7"W x 24.5"D x 53.2" to 59.2"H (adjustable)
 Weight: 330 lbs.
 Table Height: 34.2 to 40.1" (adjustable)
 Strap Size: 5mm, 6mm, 9mm width x .014" to .025" thickness
 Core Size: 8" ID x 8" Face
 Power Requirements: 110V, Single phase 50/60 Hz, 5 Amps



OPERATOR FRIENDLY RECESSED CONTROL PANEL

AVAILABLE ARCH SIZES

Width \ Height	21.6" 550mm	25.6" 650mm	33.5" 850mm	41.3" 1050mm	49.2" 1250mm	65.0" 1650mm
11.8" 300mm		✓				
15.7" 400mm	✓		✓			
19.7" 500mm		✓	✓		✓	✓
23.6" 600mm			✓			
31.5" 800mm			✓	✓	✓	
39.4" 1000mm				✓	✓	



ADJUSTABLE PHOTO EYE FOR AUTOMATIC STRAPPING



COMPACT, LOW MAINTENANCE CONTROL HEAD

